LAMPIRAN

Menurut kepustakaan λ SUTM dan SKTM masing-masing 0,2 dan 0,07, sedang kenyataannya masing-masing 1,4 dan 0,251 yang berarti masing-masing hampir 7 dan 3,6 kali lebih besar. Karena besarnya λ kenyataan ini, maka λ (dan tentunya f) komponen-komponen yang lain dapat diabaikan.

Berbeda dengan λ dan f maka nilai d yang diperoleh dari laporan Gangguan tersebut dalam Ayat 18 di atas tidak jauh berbeda dengan Lampiran B dan karenanya d dari Lampiran B dapat dipakai.

Oleh karena itu indeks keandalan kelima konfigurasi jaringan yang direncanakan di lingkungan PLN dapat diperoleh dengan memperbandingkannya dengan nilai-nilai f dan d dari Lampiran B dan C, yaitu:

(a) SUTM radial : f = 3,2 kali/tahun

: d = 21 jam/tahun

PERHITUNGAN INDEKS KEANDALAN SISTEM DISTRIBUSI 20 KV PENYULANG BSB 2 DENGAN METODE FMEA (FAILURE MODE EFFECT ANALYSIS) DAN SECTION TECHNIQUE DI PT. PLN ULP BOJA

ORIGINALITY REPORT

22%	20%	0%	14%
SIMILARITY INDEX	INTERNET SOURCES	PUBLICATIONS	STUDENT PAPERS

PRIMARY SOURCES

1	text-id.123dok.com Internet Source	5%
2	www.digilib.its.ac.id Internet Source	3%
3	media.neliti.com Internet Source	3%
4	Submitted to Universitas Muhammadiyah Yogyakarta Student Paper	2%
5	id.123dok.com Internet Source	2%
6	docplayer.info Internet Source	1%
7	pt.scribd.com Internet Source	1%

berderet.blogspot.com

Dedi Nugroho, ST. MT.

Dr. Ir. H. Muhamad Haddin, M.T.